

Clock Blithfield DS (Double-sided) (Multi-fuel 10kW)

	KVV)						
			C			T	
Dimensions	A		В	С		Weight	
Clock Blithfield DS	k Blithfield DS 535mm		600mm	600mm 175kg		175kg	
Description			Values				
Fuel Type			Wood-Burning and Multi-Fuel				
Output Range			8.5kW – 14kW (Nominally Tested at 10.5kW)				
Energy Rating			A				
Flue Size			6" / 150mm				
Glass Size			352mm x 270mm PATENTPENUI				
Rope Size			12mm Diameter Soft				
Warranty			7 Years* (See back page for details)				
Available Options (Additional Cost)		Distano	ce to Materials	Above	Sides	Back	
Colours - See Colour Chart on p22		nbustibles	550mm	850mm	N/A		
Brass or Stainless Steel Fittings To Non-			-combustibles	375mm	200mm	N/A	
Direct Air Kit							

	(VV)					
			C			T
Dimensions	А		В	с		Weight
Clock Blithfield DS	Clock Blithfield DS 535mm		600mm	600mm	ı	175kg
Description			Values			
Fuel Type			Wood-Burning and Multi-Fuel			
Output Range			8.5kW – 14kW (Nominally Tested at 10.5kW)			
Energy Rating			A			
Flue Size			6" / 150mm			
Glass Size			352mm x 270mm			
Rope Size			12mm Diameter Soft			
Warranty			7 Years* (See back page for details)			
Available Options (Additional Cost)		Distanc	e to Materials	Above	Sides	Back
Colours - See Colour Chart on p22		bustibles	550mm	850mm	N/A	
Brass or Stainless Steel Fittings To Nor		-combustibles	375mm	200mm	N/A	
Direct Air Kit						

(Iviuiti-iuei iui	\ 						
			• C				
Dimensions	A		В	с		Weight	
Clock Blithfield DS	DS 535mm		600mm	600mm	ı	175kg	
Description			Values				
Fuel Type			Wood-Burning and Multi-Fuel				
Output Range			8.5kW – 14kW (Nominally Tested at 10.5kW)				
Energy Rating			A				
Flue Size			6" / 150mm				
Glass Size			352mm x 270mm PATENT PENUIT				
Rope Size			12mm Diameter Soft				
Warranty			7 Years* (See back page for details)				
Available Options (Additional Cost)			Distance to Materials		Sides	Back	
Colours - See Colour Chart on p22		To Corr	nbustibles	550mm	850mm	N/A	
Brass or Stainless Steel Fittings To Non		-combustibles	375mm	200mm	N/A		
Direct Air Kit For best p			erformance we recomn	nend these distar	nces to non-com	bustible materials.	

Clock stoves must be placed on a hearth with a minimum thickness of 12mm.



www.clockwoodburners.co.uk